











	0.00	-				
	MINI		MIDI	MAXI	MAXI	
	nanoPAC-300P	nanoPAC-500	powerPRO-300	powerPRO-500	powerPRO-3AMP	
Output range Volts Current Power Resolution	10-300V 10-400mA 60W max. 1V / 1mA	10-500V 10-400mA 120W max. 1V / 1mA	5-300V 1-700mA 150W 1V / 1mA / 1mW	5-500V 1-800mA 300W 1V / 1mA / 1W	5-300V 10-3000mA 300W 1V / 1mA / 1W	
Type of output	constant voltage or constant current		constant voltage, constant current or constant power, programmable			
Automatic crossover	-	-	~	~	v	
Timer	1-999 min. with alarm; intensity continuous		constant mode: 1-999 min. with alarm; continuous. programmable mode: 1-999 min. with alarm; continuous.			
Pause/resume function	v	✓	✓	✓	✓	
Display	3-digit LED	3-digit LED	2.4" LCD display	2.4" LCD display	2.4" LCD display	
Programmable Methods	2 step-program	2 step-program	Up to 30 programmable files, each with 6 steps. Preset options for Cleaver gel tanks.			
Safety features	no load detection; shrouded plugs and sockets; over temperature protection; over load detection		no load detect; leakage detect; over temperature protection; over load detection; sudden load change detection (could be disabled by proper setting); shrouded plugs and sockets			
Operating conditions	ambient-40°C; ±95% humidity	ambient-40°C; ±95% humidity	ambient-40°C; ±95% humidity	ambient-40°C; ±95% humidity	ambient-40°C; ±95% humidity	
Stackable	х	x	~	~	v	
Number of output jacks	2 sets in parallel	2 sets in parallel	5 sets in parallel	5 sets in parallel	5 sets in parallel	
Regulatory conformity	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC	ETL, CE, FCC	
Rated voltage	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC	
Construction	polycarbonate housing with aluminium base		flame retardant ABS-plate design			
Dimensions (WxDxH)	140 x 191 x 84mm	140 x 191 x 84mm	215 x 335 x 104mm	215 x 335 x 104mm	215 x 335 x 104mm	
Weight	1kg	1kg	2.1kg	2.1kg	2.1kg	



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.