


KERN AXE 200-4

KERN

Entry level analytical balance with compact housing and internal adjustment



Category

Brand	KERN
Product category	Laboratory balance
Product group	Analytical balance
Product family	AXE

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Force compensation
Weighing capacity [Max]	220 g
Readability [d]	0,0001 g
Reproducibility	0,0002 g
Linearity	± 0,0003 g
USP Minimum weight of sample (k = 2, U = 0.1%)	400 mg
Resolution	2.200.000
Tare range	220 g

Adjustment options Internal calibration (automatic)

Recommended adjusting weight 200 g (E2)

Stabilization time 3 s

Warm-up time 8 h

Eccentric loading at 1/3 [Max] 0,0003 g

Maximum creep (15 minutes) 1 mg

Maximum creep (30 minutes) 2 mg

Default unit g

Units g
mg
ct
oz

Display

Display type LCD

Display backlight	✓
Display screen size	96x24 mm
Display segments	7
Display digit height	16 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	195×300×295 mm
Dimensions rectangular draught shield - inner (W×D×H)	175×150×205 mm
Dimensions rectangular draught shield - outer (W×D×H)	180×175×200 mm
Dimensions weighing surface (Ø)	80 mm
Dimensions weighing surface	80 mm
Material housing	ABS plastic
Material weighing plate	stainless steel
Material draught shield	glass
Material display housing	Plastics
Level indicator	✓
Levelling feet adjustable	✓

Functions

Recipe/summing level	Rez A (Net total)
Percentage determination	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	220.000
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Reference quantity	5, 10, 20, 50, 100, 200
Peak function	✓
Tare function	manual (multi)
Number of keys for operation	5

Interface

Interfaces RS-232 standard

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH

KERN AXE 200-4



Entry level analytical balance with compact housing and internal adjustment

Input voltage power supply / 100 V - 240 V AC, 50 /
power [Max] 60 Hz

Input voltage device / power [Max] 9 V, 3 A

Environmental conditions

Ambient temperature [Min] 15 °C

Ambient temperature [Max] 25 °C

Humidity of environment [Min] 20 %

Humidity of environment [Max] 85 %

Use temperature [Min] 15 °C

Use temperature [Max] 25 °C

Storage temperature [Min] -10 °C

Storage temperature [Max] 40 °C

Approval

CE mark ✓

Services (optional)

Article number for DAkkS
calibration 963-101

Article number for certificate of
conformity 969-517

Packing & Shipping

Delivery time 1 d

Dimensions packaging (W×D×H) 320×430×415 mm

Shipping method Parcel service

Net weight approx. 5,0 kg

Gross weight approx. 8 kg

Shipping weight 11,4 kg

Pictograms

STANDARD



OPTION





WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.