Pharmacy Plus Bluetooth Enabled Refrigerator

47L Pharmacy Plus Upright Fridge with Solid Door

GDMAcode	PPSR47BT-UK
SKU code	444411305





Key features

- ✓ Local monitoring and alarm history via Bluetooth
- \checkmark Power failure alarm with backup battery powered recording
- \checkmark Solid and glass door options

 \checkmark Intelligent fan management system for enhanced performance



Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.

Specification: 47L Pharmacy Plus Upright Fridge with Solid Door

Nate displaying201Unit Exerce Velocity4.55 cmUnit Exerce Velocity5.50 cmPacket Velocity		
Link Torons Dep MarkAdd SymmUnit Exerner Legist (wm)Add SymmUnit Exerner Legist (wm)Add SymmData Weigh (wh)Add SymmPacket Dep ImmAdd SymmPacket Dep ImmAdd SymmData Mark Weigh (wh)Add SymmData Mark Weigh (wh)Add SymmData Mark Weigh (wh)Add SymmData Mark Weigh (wh)Add SymmData Mark Mark Mark Mark Mark Mark Mark Mar	Gross Capacity (litres)	47L
Ush Baran Lingding4.4.4.mmInstance Stapping5.5.0.mgInstance Stapping7.5.0.gInstance Stapping7.5.0.gPacked Medging Full7.5.0.gPacked Medging Full7.5.0.gPacked Medging Full7.5.0.gStapping7.5.0.gPacked Medging Full7.5.0.gStapping Full		
Unit Education550m/mResider Weigh (trai)7.5 SigResider Weigh (trai)7.5 SigResider Weigh (trai)7.5 SigResider Weigh (trai)2.5 SigDevelope (train)2.5 SigResider Weigh (trai)2.5 SigResider Weigh (trai)7.5 SigDevelope (train)7.5 SigDevelope (train)7.6 SigDevelope		
Product Weight fightProcess Weight fightProcess Weight fightProcess Weight fightDecome of VeightConstruct SeriesConstruct Series<		
Basiat Main yon)444mmBasiat Nation yon550mmBasiat Solution yon550mmBasiat Solution yon550mmBasiat Solution yon210mmBasiat Solution yon210mm <tr< th=""><th></th><th></th></tr<>		
Backs Depis fromSoftmanBacks Depis fromSoftmanBecket Weigh fromPainers SoftmanBecket Weigh fromPainers SoftmanBecket Weigh fromPainers SoftmanBecket Weigh fromSoftmanBecket Becket Weigh fromSoftmanBecket Becket Weigh fromSoftmanBecke		
Backet Weige (m)6400mmCantry of sign1/3640Cantry of sign0.0000Cantry of sign0.00000Cantry		
Pecket WorksLikksInstance Distry of Origin		
County of bigUkKampet and base and some Xuber of X		
internal Densides (zmm) (MODB)4.000000000000000000000000000000000000		
Tempositive Brands122 to 1192ColurWh/NDC/conExternal FinishFinitive SteeldExternal Finish11859Steeld Of HES/R58 mix()2010Door SpinPranted Steeld FieldDoor SpinDoor SpinDoor Spin11859Number of Door Tray11859Number of Door Tray Parliese114Door Spin114Door Spin114Do		
ColourWithing/ConventExternal FinishDistrictural SteelInternal FinishSite SteelDear FinishSite SteelDear FinishParted Steel/SteelDear FinishParted Steel/SteelDear FinishHighDear FinishHighReadownHighReadownHighAdjustable FinishHighParthead StaeHighParthead StaeHigh		
Exernal FinishPointerst StraidType of platkStritt DDD (11975/DLST String)Straid StraidStritt DDD (11975/DLST String)Straid StraidStritt DDD (11975/DLST String)Straid StraidStritt DDD (11975/DLST String)Straid StraidStritt DDD (11975/DLST Straid)Number of DDD Type StraidStraid StraidStraid StraidStraid StraidStraid StraidStraid StraidStraid Straid StraidStraid StraidStraid Straid StraidStraid StraidStraid Straid Straid StraidStraid StraidStraid Straid Strai	Temperature Range	+2°C to +8°C
internal FinishHHP*Book Tipps of plantsStalt StaltBook Typs of plantsPainted StaltBook TypsStaltBook TypsStaltBook TypsHingst Stanty StaltBook TypsHingst Stanty StaltBook TypsAttaltBook TypsAttaltBook TypsAttaltBook TypsAttaltBook TypsAttaltBook TypsAttaltBook TypsAttaltBook Type StaltAttaltBook Type StaltYesBook Type StaltYes<	Colour	White/Green
Type of plateSPI B00 (HPSAS mu)Deer IninParlies Steel / SolidDeer TypeSolid / SolidDeer TypeSolid / SolidDeer SyleFiguNumber of Door TrysNumber of Door TryNumber of Door TryYes 2 AddAlpisable Feel (number & Southanne)Yes 2 AddAlpisable SizeNomPertolsYes 2Number of Solucial OneYes 2Solucial OneYes 2Number of Solucial OneYes 2Solucial OneYes 2Solucial OneYes 2Solucial OneYes 2Solucial OneYes 2Solucial OneYes 2Solucial	External Finish	Painted Steel
Does FindsPeriod SolidDoes TypeSolidDoes TypeSolidDoes TypeSolidDoes TypeSolidDoes UterSolidDoes Uter TypeSolidDoes Type PeriodsSolidDoes Does TransSolidDoes TransSolidDoes TransSolidDoes TransSolidDoes TransSolidDoes TransSolidSolid Solid Solid MonoSolidDoes TransSolid SolidDoes TransSolid SolidDoes TransSolid SolidDoes TransSolid SolidSolid Solid SolidSolid SolidDoes TransSolid SolidDoes TransSolid SolidDoes TransSolid SolidDoes TransSolid SolidDoes TransSolid Solid <th>Internal Finish</th> <th>HIPS*</th>	Internal Finish	HIPS*
Door TypeNotifiedDoor TypeHitsenderDoor TrypHitsenderNumber of Door Tryp PositionsN/NStep Copen Dop Tryp PositionsN/NReplacement Door SealN/NReplacement Door SealN/NReplace SealN/N <th>Type of plastic</th> <th>SRL800 (HIPS/ABS mix)</th>	Type of plastic	SRL800 (HIPS/ABS mix)
Door signI.Ingr.dt. ReversibleNumber of box Trays	Door Finish	Painted Steel / Solid
Door LinerLinerNumber of Door Tay PositionsNANumber of Door Tay PositionsNABeploarment Door SealNoOpen Open Door SeriesNoSeploarment Door SealNoOpen Door SeriesYesLockYesSeptomer SeriesNoDoor Upen Door SeriesYesLockRead LifetionsBerthadNoBerthad SectorRead LifetionsBerthad SectorNoPortube SizeNoBerthad SectorNoNomber of SealNoBerthad SectorNoBerthad SectorNoBerthad SectorNoBerthad SectorNo <th>Door Type</th> <th>Solid</th>	Door Type	Solid
DorumeFlitNumber of Dor Tay PositionsP(A)Number of Dor Tay PositionsP(A)Bablesment Dor SailP(A)Bablesment Dor SailP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment PolyP(K)Bablesment Po	Door Style	Hinged, Reversible
Number Obor Traysn/aNumber Obor Traysn/aDer Open Depth Imm)905mmDer Open Depth Imm)905mmOpen Dept SearNoOpen Dept SearNoDer Open SearsYesLockYesDer Open SearsYesDer Open SearsYesDer Open SearsYesDer Open SearsYesDer Open SearsYesDer Open SearsYesBerthels SeaNoBerthels SearYesTemperature Diploy on PanelYesTemperature Diploy on PanelYesTemperature Diploy on PanelYesTemperature Diploy on PanelYesSeart MarkYesSeart MarkYesSeart MarkYesNumber of SherbeOlowersYesNumber of SherbeOlowersYesSherb MarcalPolyhene Coated WireDer SherbeOlowersYesSherbeSterlingOpen SherbeOlowersDer Open SherbeOlowersYesSherbeSterlingYesDer Open SherbeOlowersYesSherbeSterlingYesDer Open SherbeOlowersYesSherbeSterlingYesDer Open SherbeOlowersYesSherbeSterlingYesD	Door Liner	
Number of boor Tay Positions)n/aBeblement Door Seal%DrmmBeblement Door Seal%DrmmBeblement Door SealWesGoor Door SealWesGoor Door SealWesSubtable Feet (under seal seal seal seal seal seal seal seal		
Deor Depth (rm)ObserOpen Des SharorNoOpen Des SharorNoCockNes 2. KoysAljustable (front)Nes 2. KoysAljustable (front)Nes 2.Pettole Des SharorNes 2.Tempesture Display on BandNes 2.Tempesture Display on SharorNes 2.Remote Alarm ContactsNes 2.Number of Sher Positions1Shert MacrialNes 2.Shert MacrialNes 2.Shert MacrialNes 2.Drawer Sher PositionsAlarm ContactsShert MacrialNes 2.Drawer Shert PositionsNes 2.Shert MacrialNes 2.Drawer Shert PositionsNes 2.Shert MacrialNes 2.Drawer Shert PositionsNes 2.Des		
Replacement Door SealNoDoor Door SnowYen,LockYen,Lock (mohr & position)2 adjutatie (front)Portole SizeYen,Portole SizeNoPortole SizeNoPortole SizeNoPortole SizeYen,Portole SizeYen,Portole SizeYen,Portole SizeYen,Portole SizeYen,Portole SizeYen,Portole SizeYen,Portole SizeYen,Number Of Shelves/DowersYen,Number Of Shelves/Dowers1Number Of Shelves/Dowers1Number Of Shelves/Dowers1Sheft Size (rm) (WxD4H)Polythene Coated WireDrawer MaterialPolythene Coated WireDrawer Size (rm) (WxD4H)Yen,Drawer Size (rm) (WxD4H)Yen,Dister (Ight Activation)Yen,Dister (Ight Activation)Yen,Dister (Ight Activation)Yen,Dister (Ight Activation)Yen,Dister (Ight Activation)Yen,Dister (Ight Activation)Yen,		
Open Door SensorVes.LockYes.2.KeysAdjurabs Feet (number & position)2.adjurabs (front)PertoleYes.2PertoleYes.2PertoleNew Jes.Pertole Size1000000000000000000000000000000000000		
LockYes/S Key/SAdjatable Fert (mbre 8 position)2 adjustable (Form)Porthole SizeNesPorthole SizeNesPorthole SizeNesPorthole SizeNesPorthole SizeNesTemperature Diagon PanelNesTemperature Diagon PanelNesTemperature Diagon PanelNesRemote Alarn ContatsNesAudiba AlarnsNesNumber of Shelve/Drawers1Number of Shelve/Drawers3Sheft Size (rm) (WxDH)Adibia AlarnsSheft Size (rm) (WxDH)NesDrawer Stacing (WxDH)NesDrawer Stacing (WxDH)NesDrawer Stacing (WxDH)NesDrawer Stacing (WxDH)NesDrawer Stacing (WxDH)NesDrawer Stacing (WxDH)NesDefense Costed WireNesData Staft Stacing (WxDH)NesDefense Costed WireNesStaft Stacing (WxDH)NesStaft Stacing (WxDH)NesDefense Costed WireNesStaft Staft St		
Adjustable fetcinn/ber? adjustable from/PortholeVeSPorthole issiceVeSPorthole issiceNerrerPorthole issiceNerrerTemperature Display on PanelVeSTemperature Display on PanelVeSTemperature Display on PanelVeSRennet Alarm ContactsVeSAudites AlarmsVeSNumber of ShelveS/Texes1Number of ShelveS/Texes1Number of ShelveS/Texes3Shelf JakemalPolythene ContactsNumber of ShelveS/Texes1Number of ShelveS/Texes1Number of ShelveS/Texes1Shelf JakemalPolythene Contact WireDrawer HaerialNoNumber of ShelveS/Texes1Drawer HaerialNoDrawer	-	
PortholeYesPorthole StaceIBornmPorthole StaceYesPorthole StaceYesTemperature Dalign on PaneloYesTemperature Dalign on PaneloYesRemote Alarm ContestYesAudibe AlarmsYesVisual AlarmsYesNumber of ShahverDownen1Number of ShahverDownen1Shaff Stace (mn) (WxDath)Alform x 200mm x 6mmShaff Jace (mn) (WxDath)Polythene Coatted WireDrawer Stace (mn) (WxDath)Polythene Coatted WireDrawer S		· · · · · · · · · · · · · · · · · · ·
Dethole isola Isom Porthole isolan Rear LI Corner Temperature Display on Panel Yes Audible Alarms Yes Audible Alarms Yes Audible Alarms Yes Number of SteleveDravers 1 Number of SteleveDravers 1 Stelf Stac (rml) (WxDxH) Alarms 200mm x form Draver Matchial Polythene Coated Wire Draver Stac (rml) (WxDxH) Rester Draver Stac (rml) (WxDxH) Rester Draver Stac (rml) (WxDxH) Rester Stack Stac (rml) (W		
Parthel coationPast LH CortinarTemperature Diagley on PanelYesTemperature Diagley on PanelYesTemperature Diagley on PanelYesAuditel AarmsYesVisual AarmsYesNumber of Shafvers/Drawers1Number of Shafvers/Drawers1Shaff Size (nm) (WxDati)416mm x 200mm x 6mmShaff Size (nm) (WxDati)1Drawer Siz (nm) (WxDati)1Drawer Siz (nm) (WxDati)1Drawer Size (nm) (WxDati)1Drawer Size (nm) (WxDati)1Basket Size (nm) (WxDati)2Basket Size (nm) (WxDati)3Basket Size (nm) (WxDati)3B		
Temperature Display on PanelYesTemperature AamYesPemote Alum ContactsYesAudite AlamsYesNumber of Shelves/Dravers1Number of Shelves/Dravers1Number of Shelves/Dravers1Shelf Sactions3Shelf Sactions3Shelf Sactions1Draver Size (mm) (WxDxH)4/Gram x 200mm x GramDraver Size (mm) (WxDxH)0Draver Size (mm) (WxDxH)0Draver Size (mm) (WxDxH)0Basket Material0Draver Size (mm) (WxDxH)0Size (mm) (WxDxH)0Basket Material0Deriver Size (mm) (WxDxH)0Basket Material0Deriver Size (mm) (WxDxH)0Basket Material0Deriver Material0Material0Deriver Material0Deriver Material0Deriver Material0		
Temperature AarmYesAudite of NortestYesAudite of NortesYesAudite of Nortes/Dravers1Number of Shoft Positions3Sheff Sacem(WADAH)Additem X SommSheff Sacem(WADAH)Additem X SommDraver NaterialPolythene Coated WireDatext Size (mm) (WADAH)366m X SiSom X SommDraver NaterialPolythene Coated WireDatext Size (mm) (WADAH)366m X SiSom X SommDraver NaterialPolythene Coated WireDatext Size (mm) (WADAH)366m X SiSom X SommDraver Size (mm) (WADAH)366m X SiSom X SommDraver Size (mm) (WADAH)366m X SiSom X SommDraver Size (mm) (WADAH)366m X SiSom X SommDire (Jph Liph LiphYesUph TypeLEPUght AttivationDoor Switch / ControllerFanNoSource (Stress)NoSource (Stress)NoSource (Stress)NoSource (Stress)NoNoNoNoYesNoNoNoYesSource (Stress)YesSource (Stress)YesSource (Stress)YesSource (Stress)YesSource (Stress)Yes<		
Permote Alurm Contacts Yes Visual Alarms Yes Visual Alarms Yes Visual Alarms 1 Number of Shelf Positions 3 Shelf Xis (mm) (VXDXH) 4/Emm x 200mm x 6mm Shelf Xis (mm) (VXDXH) Polythme Costed Wire Draver Size (mm) (VXDXH) Na Draver Material Polythme Costed Wire Basket Material Polythme Costed Wire Basket Material Polythme Costed Wire Basket Material Door Switch / Controller Upt Type LED Door Switch / Controller No Defores testing Ault (Off Cycle) Controller Type Digital B1, External Bluetoch Yes Nr Yes Nr Yes Refigrant Type Air & Lod (Cycle) Controller Ty		
Audibe Alarms Yes Number of Sholvs/Drawers 1 Number of Sholvs/Drawers 1 Number of Sholvs/Drawers 3 Sheff Sic (mm) (WxDxH) 41Gmm x 200mm x Gmm Sheff Material Polythene Coated Wire Drawer Material Polythene Coated Wire Drawer Material Polythene Coated Wire Drawer Material Polythene Coated Wire Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) Strem X Borm m X Borm m X Borm m Interior Light Yes Dial Stack Size (mm) (WxDxH) Strem X Borm m X Borm m X Borm m Interior Light Yes Space Transmer Size X Light Noted Strem All Strem All Darket Size (mm) (WxDxH) Strem All Darket Size (mm) (WxDxH) Strem All Dial Actor (MxDxH) Strem All Dial Actor (Dirythene Coated Wire Strem All Basket Size (mm) (WxDxH) Strem All Dial Controller (MxDxH) Dial Controller (Mire Strem All Strem Size X Light Activation No Basket Size (mm) (XxDxH) Strem	Temperature Alarm	
Vaual armsYesNumber of Shelf Positions1Number of Shelf Positions3Shelf Sice (mm) (WACXH)416mm x 200mm x 6mmShelf Sice (mm) (WACXH)Polythene Coatted WireDrawer Size (mm) (WACXH)Polythene Coatted WireDasket MaterialPolythene Coatted WireBasket Size (mm) (WACXH)396mm x 165mm x 150mmInterior LightYesLight ActivationDoor Switch / ControllerFanVesSpark FreeDoor Switch / ControllerFanNoDefords settingAuto (Off Cycle)Controller TypeDigital BT. ExternalBluetoothYesWirPNoNoYesWirPAir K Load (Clycol Solution)Ambient Temperature RangeYesWirPAir K Load (Clycol Solution)Ambient Setter Sack WareYesHGC FreeYesWire SolutionYesMore SolutionYesMore SolutionYesMore SolutionYesMore SolutionYesMore SolutionYesMiner SolutionYesMore SolutionYesMiner SolutionYesMiner SolutionYesMiner SolutionYesMore SolutionYesMiner SolutionYesMiner SolutionYe	Remote Alarm Contacts	Yes
Number of Shelves/Dravers 1 Number of Shelf Positions 3 Shelf Material Alform x 200mm x form Shelf Material Polythene Coated Wire Draver Size (mm) (WxDxH) Na Draver Material Polythene Coated Wire Draver Material Na Draver Material Polythene Coated Wire Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) 396mm x 166mm x 150mm Daraver Material Polythene Coated Wire Basket Size (mm) (WxDxH) 396mm x 160mm x 150mm Daraver Size (mm) (WxDxH) S96mm x 160mm x 150mm Basket Size (mm) (WxDxH) Door Switch / Controller Fan Ves No Spark Free No No Defrost setting Autor (Off Cycle) Controller Yves Bluetooth Ves No No Nref No No No Miref Free No No No Wiff No No No No Wife Free No	Audible Alarms	Yes
Number of Shelf Positions 3 Shelf Size (mm) (WxDxH) 416mm x 200mm x 6mm Drawer Size (mm) (WxDxH) N/a Drawer Size (mm) (WxDxH) 1 Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Basket Size (mm) (WxDxH) 396mm x 165mm x 150mm Digit All (Controller Fise Ves Spark Free No Spark Free No Spark Free No Spark Size (mm) (model Size (material Si	Visual Alarms	Yes
Shelf Sie (mm) (WxDxH) 416mm x 200mm x 20mm Shelf Material Polythene Coated Wire Drawer Size (mm) (WxDxH) N'a Drawer Material N'a Drawer Material N'a Basket Material Polythene Coated Wire Basket Size (mp) (WxDxH) 399mm x 150mm Basket Size (mp) (WxDxH) 399mm x 150mm Basket Size (mp) (WxDxH) 399mm x 150mm Interior Light Yes Light Type LED Light Type Door Switch / Controller Fan Oxor Switch / Controller Spark Free No Defrost setting Auto (Off Cycle) Controller Type Digital IS 1, External Bluetooth Yes No Yes WiFi No Number of Probs Q Probe Type Alf & Load (Clycal Solution) Ambient Temperature Pange No Vies Yes WiFi Yes Start Probe Yes Vies Yes	Number of Shelves/Drawers	1
Sheif MaterialPolythene Coated WireDrawer Stee (mm) (WXDxH)n/aNumber of Basketsn/aNumber of Baskets1Basket MaterialPolythene Coated WireBasket Stee (mm) (WXDxH)396mm x 165mm x 165mm x 165mm x 105mmBasket Stee (mm) (WXDxH)396mm x 165mm	Number of Shelf Positions	3
Drawer Size (mm) (WXDXH)n/sDrawer Materialn/sDrawer Materialn/sBasket Size (m) (WXDXH)Polpthene Coated WireBasket Size (m) (WXDXH)Polpthene Coated WireLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerFanNoDefrost settingAuto (Off Cycle)Controller TypeDigital BT, ExternalBluetoothYesNoYesBluetoothYesNPCYesWIFINoNumber of ProbesQProbe TypeAlf & Load (Clycol Solution)Ambient Temperature BargeNoProbe TypeYesMIFC FreeYesHFC FreeYesMIS PinBugYesMIS PinBug<	Shelf Size (mm) (WxDxH)	416mm x 200mm x 6mm
Drawer Material n/a Number of Baskets 1 Basket Material Polythene Coated Wire Basket Size (mm) (WXDH) 396mm x 150mm Basket Size (mm) (WXDH) Yes Light Type LED Light Activation Door Switch / Controller Fan Door Switch / Controller Spark Free No Defrost setting Auto (Off Cycle) Controller Type Digital ET, External Battery Back Up/Hours No Battery Back Up/Hours No Suetooth Yes WiFi No Number of Probes 2 Probe Type Aito (Cyccl Solution) Ambient Temperature Range No No No Refrigerant Type Yes CF Free Yes MCF Free Yes Minonia Free Yes MCF F	Shelf Material	Polythene Coated Wire
Number of Baskets1Basket Size (nm) (WXDxH)Polythene Coated WireBasket Size (nm) (WXDxH)396mm X155mm X150mmInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYes - AxialSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital BT, ExternalBattery Back Up/HoursNoBluetoothYeesNrCYeesWiFiNoNumber of Probes2Probe TypeAir & Load (Clycol Solution)Armber Temperature RangeNoRefrigerant TypeProseCF FreeYeesWIFIYeesKFC FreeProseWIFI TypeProseWiff Temperature RangeNoRefrigerant TypeYeesKFC FreeYeesWIFI TypeYeesWIFI TypeYeesWIFI Temperature RangeYeesWIFI TypeYeesWIFI TypeYee	Drawer Size (mm) (WxDxH)	n/a
Basket Material Polythene Coated Wire Basket Size (mm) (WXDXH) 336mm x165mm x150mm Basket Size (mm) (WXDXH) 336mm x165mm x150mm Interior Light Type EED Light Ype ED Light Activation Door Switch / Controller Fan Yes - Axial Spark Free No Defrost setting Auto (Off Cycle) Controller Type Digital BT, External Battery Back Up/Hours No Butetooth Yes WIFI No Number of Probes Q Probe Type Air & Load (Clycol Solution) Ambient Temperature Range 10°C to 32°C Refrigerant Type RE600a CFC Free Yes MCF Free Yes <tr< th=""><th>Drawer Material</th><th>n/a</th></tr<>	Drawer Material	n/a
Basket Size (mm) (WxDxH)3996mm x 165mm x 150mmInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYes - AxialSpark FreeNoDefrost settingOligital BT, ExternalBattery Back Up/HoursOligital BT, ExternalBattery Back Up/HoursNoBluetoothYesNoYesWiFiNoNumber of ProbesQProbe TypeAite Cicyclo Solution)Armiter Temperature RangeNoRefrigerant TypeNoOther Plug Types AvailableYesVif S IP IngligYesVif S IP IngligYesOther Plug Types AvailableYesOther Plug Types AvailableYesVit S IP IngligYesOther Plug Types AvailableYesVit S IP IngligQuerterCharles SupplyYesOther Plug Types AvailableYesVit S IP IngligQuerterCharles SupplyYesAntimonia FreeHigh Density Polyuruthane FoamInsulation TypeHigh Density Polyuruthane FoamBlowing AgentCyclopentaneAntim Kickes (mm)YesWall BracketsNoOptional Driver SystemNoOptional Driver SystemNoOptional Driver SystemNoOptional Driver SystemNoOptional Driver SystemNoOptional Driver SystemNo	Number of Baskets	1
Interior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanOr Yes - AxialSpark FreeNoSpark FreeOn Or Olf Cycle)Controller TypeOn Digital BT, ExternalBattery Back Up/HoursNoBluetoothYesNFCNoWiFiOn NoNumber of Probes2Probe TypeAris Load (Clycol Solution)Ambient Temperature RangeOf YesAmbient Temperature RangeYesAmonia FreeYesKTC FreeYesAmonia FreeYesUts 3 Pin Light SpesitionYesAmonia FreeYesChrose spepitionYesAmonia FreeYesBuildon Type ShalabeYesOther Plug Types AvailabeYesSpark FreeAdormBluint Torperature RangeHigh Density Polyurothane FoamBiowing AgentGradenOther Dig Types AvailabeYesOther Dig Types AvailabeYesWill Brobensity Polyurothane FoamHigh Density Polyurothane FoamBiowing AgentChrose (Mercine)Att Microbil HandleYesWall BrobensityYesWall BrobensityYesWall BrobensityYesSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoState FreeSpark FreeState FreeSpark Free <th>Basket Material</th> <th>Polythene Coated Wire</th>	Basket Material	Polythene Coated Wire
Interior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanOr Yes - AxialSpark FreeNoSpark FreeOn Or Olf Cycle)Controller TypeOn Digital BT, ExternalBattery Back Up/HoursNoBluetoothYesNFCNoWiFiOn NoNumber of Probes2Probe TypeAris Load (Clycol Solution)Ambient Temperature RangeOf YesAmbient Temperature RangeYesAmonia FreeYesKTC FreeYesAmonia FreeYesUts 3 Pin Light SpesitionYesAmonia FreeYesChrose spepitionYesAmonia FreeYesBuildon Type ShalabeYesOther Plug Types AvailabeYesSpark FreeAdormBluint Torperature RangeHigh Density Polyurothane FoamBiowing AgentGradenOther Dig Types AvailabeYesOther Dig Types AvailabeYesWill Brobensity Polyurothane FoamHigh Density Polyurothane FoamBiowing AgentChrose (Mercine)Att Microbil HandleYesWall BrobensityYesWall BrobensityYesWall BrobensityYesSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoState FreeSpark FreeState FreeSpark Free <th>Basket Size (mm) (WxDxH)</th> <th>396mm x 165mm x 150mm</th>	Basket Size (mm) (WxDxH)	396mm x 165mm x 150mm
Light TypeLEDLight ActivationDoor Switch / ControllerFanOper Switch / ControllerSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeOpligital LockBattery Back Up/HoursNoBittery Back Up/HoursNoBittery Back Up/HoursNoBittery Back Up/HoursYesWiFiNoNoYesWiFiNoNumber of Probes2Probe TypeAir & Load (Glycol Solution)Ambient Temperature PangeNoHfC FreeYesMife FreeYesUK Spi PlugYesVotage SupplyYesCher PigYesMife Tropes PiplingYesMife FreeYesHfC FreeYesMife Sin PlugYesUK 3 Pin PlugYesUkitage SupplyYesOther Plug Types AvailableYesUkitage SupplyCyclopentaneAnti Microbial HandleYesWill BracketsYesWall BracketsYesWall BracketsNoOptional Digital LockNo	Interior Light	
Light ActivationDoor Switch / ControllerFanVes - AxialSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital BT, ExternalBattery Back Up/HoursNoBluetoothYesNFCYesWiFINoNumber of Probes2Probe TypeAir & Load (Clycol Solution)Ambient Temperature RangeICPC to 32°CRefrigerant TypeYesHCC FreeYesMTC FreeYesUX 3 Pin PlugYesUK 3 Pin PlugYesUK 3 Pin PlugYesUK 3 Pin Plug Types AvailableYesUK 3 Pin Plug Types AvailableYesUK 3 Pin Plug Types AvailableYesUkta of Type40mmInsulation Thickness (mm)YesInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Digital LockNo	Light Type	
FanYes - AxialSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital BT, ExternalBattery Back Up/HoursNoBluetoothYesNFCNoNumber of Probes2Probe TypeAitr & Load (Olycol Solution)Armbient Temperature RangeNoRefrigerant TypeNoCFC FreeYesMTFCYesMTFC FreeYesMTFC FreeYesUK 3P PlugYesOther Plug Types AvailableYesVitage SupplyYesOther SupplyYesBowing AgentCyclopentaneBowing AgentCyclopentaneAntilor TypeHigh Density Polyurothane FoamBowing AgentYesMarketsYesMarketsYesMarketsYesOptional Digital LockNoOptional Digital LockNo		Door Switch / Controller
Spark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital BT, ExternalBattery Back Up/HoursNoBluetoothYesNFCYesWiFINoNumber of Probes2Probe TypeAir & Load (Cilycol Solution)Ambient Temperature Rage10°C to 32°CRefrigerant TypeYesHFC FreeYesHFC FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage SupplyYesVoltage SupplyYesStoring TypeHigh Density Polynothane FoamBlueiton Thickness (rm)YesBlueiton TypeHigh Density Polynothane FoamBlueiton TypeYesVoltage SupplyYesStoring TypeYesStoring TypeYesStoring Type SystemYesOptional Digital LockNo	Fan	
Defrost setting Auto (Off Cycle) Controller Type Digital BT, External Battery Back Up/Hours No Bluetooth Yes Bluetooth Yes NFC Yes WIFI No Number of Probes 2 Probe Type Air & Load (Cilycol Solution) Ambient Temperature Range 10°C to 32°C Refrigerant Type ReGO0a CFC Free Yes MTCF Yes Ammonia Free Yes UK 3 Pi Plug Yes Votage Supply Yes Votage Supply Yes Insulation Thickness (mm) High Density Polyuruhane Foam Blowing Agent Cyclopentane Anti Kicrobial Handle Yes Wall Brackets Yes Optional Digital Lock No	Spark Free	
Controller TypeDigital BT, ExternalBattery Back Up/HoursNoButetoothNoBluetoothYesNFCYesWIFINoNumber of Probes2Probe TypeAir & Load (Clycol Solution)Ambient Temperature Range10°C to 32°CRefrigerant TypeYesHFC FreeYesHFC FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage SupplyYesVoltage SupplyYesBluidation Thickness (mm)40mmBluidation Thickness (mm)40mmBluidation Thickness (mm)YesBluidation Thickness (mm)<		
Battery Back Up/HoursNoBluetoothYesNFCYesNFCYesWiFINoNumber of Probes2Probe TypeAri & Load (Clycol Solution)Ambient Temperature Range10°C to 32°CRefrigerant TypeR6500aCFC FreeYesHFC FreeYesMCFC FreeYesUK 3 Pin PlugYesUK 3 Pin PlugYesVoltage SupplyYesVoltage Supply220-240VInsulation TrypeHigh Density Polyurothane FoamBlowing AgentYesAnt Microbial HandleYesOptional Drawer SystemNoOptional Digital LockNo		
Bluetooth Yes NFC Yes NIFL No WiFl No Number of Probes 2 Probe Type Air & Load (Glycol Solution) Ambient Temperature Range 10°C to 32°C Refrigerant Type R600a CFC Free Yes HFC Free Yes MICT Free Yes Ammonia Free Yes UK 3 Pin Plug Yes Voltage Supply Yes Insulation Thickness (mm) 40mm Insulation Type High Density Polyurothane Foam Blowing Agent Yes Antil Grobial Handle Yes Optional Digital Lock No		
NFC Yes WIFI No Number of Probes 2 Probe Type Air & Load (Glycol Solution) Ambient Temperature Range 10°C to 32°C Refrigerant Type R600a CFC Free Yes HFC Free Yes Ammonia Free Yes UK 3 Pin Plug Yes Other Plug Types Available Yes Voltage Supply 220-240V Insulation Thickness (mm) 40mm Insulation Type High Density Polyurothane Foam Blowing Agent Yes Anti Microbial Handle Yes Optional Drawer System No Optional Digital Lock No		
WiFiNoNumber of Probes2Probe TypeAir & Load (Clycol Solution)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCC FreeYesMumber of ProbesYesUK 3 Din PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNo		
Number of Probes2Probe TypeAir & Load (Glycol Solution)Ambient Temperature RangeOff & Load (Glycol Solution)Refrigerant TypeR600aCFC FreeR600aHFC FreeYesHFC FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNo		
Probe TypeAir & Load (Glycol Solution)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurothane FoamBlowing AgentCyclopentaneArti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesOptional Drawer SystemNoOptional Digital LockNo		
Refrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurothane FoamBlowing AgentCyclopentaneAnt Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
CFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage SupplyYesInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
HFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage SupplyYesInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
HCFC FreeYesAmmonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage SupplyYesInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
Ammonia FreeYesUK 3 Pin PlugYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
UK 3 Pin PlugYesOther Plug Types AvailableYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
Other Plug Types AvailableYesOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
Voltage Supply220-240VInsulation Thickness (mm)40mmInsulation TypeHigh Density Polyurothane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsYesOptional Drawer SystemNoOptional Digital LockNo		
Insulation Thickness (mm) 40mm Insulation Type High Density Polyurothane Foam Blowing Agent Cyclopentane Anti Microbial Handle Yes Wall Brackets Yes Optional Drawer System No Optional Digital Lock No		
Insulation Type High Density Polyurothane Foam Blowing Agent Cyclopentane Anti Microbial Handle Yes Wall Brackets Yes Optional Drawer System No Optional Digital Lock No		
Blowing Agent Cyclopentane Anti Microbial Handle Yes Wall Brackets Yes Optional Drawer System No Optional Digital Lock No		
Anti Microbial Handle Yes Wall Brackets Yes Optional Drawer System No Optional Digital Lock No		High Density Polyurothane Foam
Wall Brackets Yes Optional Drawer System No Optional Digital Lock No	Insulation Inickness (mm) Insulation Type	
Optional Drawer System No Optional Digital Lock No		
Optional Digital Lock No	Insulation Type	Cyclopentane
Optional Digital Lock No	Insulation Type Blowing Agent	Cyclopentane Yes
	Insulation Type Blowing Agent Anti Microbial Handle	Cyclopentane Yes Yes
UldSS PPUK4/UK - 444411506	Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	Cyclopentane Yes Yes No
	Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System Optional Digital Lock	Cyclopentane Yes Yes No No



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.