# Laboratory Plus Bluetooth Enabled Refrigerator

### 310L Laboratory Plus Upright Fridge with Solid Door

GDMA code LSFSR310BT-UK SKU code 444411360



#### MADE IN BRITAIN

### Key features

- $\checkmark$  Local monitoring and alarm history via Bluetooth
- ✓ Lec Medical Smartphone App compatible
- $\checkmark$  Access port Factory fitted 16mm porthole
- Spark-free interior to reduce risk of ignition



## - 43 - 41 - 44 - 44

### Bluetooth Lec Connected Sma Controller App

Local temperature monitoring and alarm history via Bluetooth connectivity.



Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.



Spark-free

We have removed

items such as fans

interior of the fridge

igniting flammable

and lights so the

has no chance of

liquids.

.

Access port

Factory fitted 16mm porthole enables quick and easy access for any secondary temperature monitoring probes.



### Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



The Experts in Medical Refrigeration



Specification: 310L Laboratory Plus Upright Fridge with Solid Door

Specification. Side Laboratory Plus opright Fridge with	
Gross Capacity (litres) Net Capacity (litres)	310L
Unit External Width (mm)	310L
Unit External Depth (mm)	595mm
Unit External Height (mm)	660mm
Product Weight (kg)	1560mm
	50.0Kg
Packed Width (mm)	640mm
Packed Depth (mm) Packed Height (mm)	660mm
Packed Height (him) Packed Weight (kg)	1560mm 57Kg
Internal Dimensions (mm) (WxDxH)	5
Temperature Range	515mm x 480mm x 1415mm +2°C to +10°C
	White/green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Painted Steel / Solid
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Balcony
Number of Door Trays	Balcony 5
Number of Door Tray Positions	9
Door Open Depth (mm)	
Replacement Door Seal	1150mm Yes
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Yes
Porthole Size	16 mm
Porthole Location	Rear Bottom
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Number of Shelves/Drawers	5
Number of Shelf Positions	9
Shelf Size (mm) (WxDxH)	495mm x 325mm x 6mm
Shelf Material	Polythene Coated Wire
Drawer Size (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	1
Basket Material	Polythene Coated Wire
Basket Size (mm) (WxDxH)	485mm x 180mm x 171mm
Interior Light	No
Fan	No
Spark Free	Yes
Defrost setting	Auto (Off Cycle)
Controller Type	Digital, External
Bluetooth	Yes
Number of Probes	1
ProbeType	Air
Ambient Temperature Range	10°C to 32°C
Refrigerant Type	R600a
UK3 Pin Plug	No
Other Plug Types Available	Yes
Voltage Supply (v)	220-240V
Insulation Thickness (mm)	45mm
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	Yes



 $\sim$ 



Pricing on any accessories shown can be found by keying the part number into the search box on our website. The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

# www.wolflabs.co.uk

Tel : 01759 301142 Fax : 01759 301143 sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.