SRTvh 1511

Laboratory refrigerator with convection cooling **Perfection**













Gross/net capacity	137/102 l
Ext. dimensions in mm (w/d/h)	597/605/819
Int. dimensions in mm (w/d/h)	450/460/620
Energy consumption in 365 days	187 kWh ¹
Ambient temperature range	+10 °C to +35 °C
Heat output	170 kJ/h
Refrigerant	R 600a
Noise output	44 dB(A)
Frequency / voltage	50/60 Hz / 220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+3 °C to +16 °C
Gradient / max. fluctuation	3.7 °C ² / 2.9 °C ³
Housing material/colour	steel / white
Door material / colour	Insulated glass door with plastic frame / white
Liner Material	commercial grade moulded polystyrol
Type of Control	2.4" touch & swipe colour display
Alarm in case of malfunction	visual and audible
Power failure alarm	immediately upon power failure for at least 12 hrs
volt-free alarm contact	yes
Connectivity type	SmartModule
Connectivity solution	integrated, removable
Interface	WiFi/LAN
Data logger	integrated, USB interface
Interior light	vertical LED light strip recessed in left wall with separate
	switch
Adjustable Shelving	3
Shelf material	wire shelves plastic-coated
Usable shelf area in mm (w / d)	450 / 425
Shelf loading	45 kg
Maximum total load	180 kg
Handle	antimicrobial handle with opening mechanism
Access ports	1 x Ø 12 mm
DIN 13277	yes
Type of lock	mechanical
Door hinges	right, reversible on site
Gross/net weight	45/43 kg
EAN-Nr.	9005382268636

 $^{^{\}mbox{\tiny 1}}$ Measured at +25 °C ambient temperature and +5 °C set temperature for fridges



and -20 °C for freezers.

² Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty,

throughout the duration.

Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.



Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel: 01759 301142

Fax: 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.