

Heavy-Duty Vortex Mixers



Heavy-Duty Vortex Mixers feature a heavy-duty design and efficient motor to permit continuous duty operation, and the ability to handle accessory components over the entire speed range. Analog variable speed models or microprocessor-controlled digital models offer exact speed control when applications demand repeatable results. A wide range of accessories are available for microtubes, microplates and a variety of tube sizes from 0.5 to 50 ml.

- Accessory Adapter's Unique Mode of Attachment Allows for Secure Mixing
- Touchpad Control & Independent LED Displays for Speed/Time on Digital Models
- Variable Speed Analog Model Offers an Economical Alternative to Digital Model

Heavy-Duty Vortex Mixers

- Designed for continuous duty
- LED displays for speed and time
- Includes foam insert for 1.5 mL to 2.0 mL microtubes

The OHAUS Digital Heavy-Duty Vortex Mixer is ideal for applications that demand repeatable results. Mixer features touchpad controls and LED displays for accurate speed (rpm) and time (minutes and seconds) results. The heavy-duty design and efficient motor allow this mixer to operate in continuous duty and handle all accessories over the entire speed range. Choose from two modes of operation: "Touch" mode for mixing tubes when cup head or Universal Holder with cover is depressed, or "On" mode when using any of the accessory attachments for continuous operation. Microprocessor control maintains set speed for strong, consistent mixing action. Timer will display elapsed time or, when programmed to user defined time limits, the unit will shut off when time reaches zero.

Operating Features:

Microprocessor Control: The variable speed microprocessor control provides consistent uniform mixing action.

LED Display: Touch pad controls with easy-to-read, independent LED displays for speed and time allow operator to view both settings at once. Provides repeatable and accurate results every time and is easily visible across lab benches. Timer will display elapsed time or, when programmed to user defined limit, will shut off unit when time reaches zero. Display will show last used settings, even after power has been turned off.

Operating Conditions:

Unit can be run in conditions from 4 to 40°C, 20% to 85% relative humidity, non-condensing.

Ordering Information:

Mixer includes a cup head, universal holder with cover, foam microtube insert for (38) 1.5 to 2.0 mL microtubes, and a detachable, 3-wire cord and specified plug. Additional accessories can be found on page 60.

This product includes:

Description	Item Number
Cup Head	30400210
Universal Holder	30400226
Universal Holder Cover	30400225
Foam Insert (1.5 to 2.0 microtubes)	30400217



Specifications		
Speed Range	On Mode Touch Mode	300 to 2500 rpm 300 to 3500 rpm
Timer		1 second to 160 hours
Orbit		4.9 mm
Controls		Touch/Standby/On Rocker Switch, LED Displays for Speed/Time, Up/Down Buttons for Set-Point Control
Capacity		1.1 kg
Duty Rating		Continuous duty
Dimensions (L x W x H)		24.1 x 16.8 x 16 cm
Ship Weight		6.8 kg

Description	Model	Item Number
Digital Heavy Duty Vortex Mixer	VXHDDG	30392136

Vortex Mixers

Heavy-Duty Vortex Mixers

- Designed for continuous duty
- Includes foam insert for 1.5 mL to 2.0 mL microtubes
- Heavy-duty design

The OHAUS Analog Heavy-Duty Vortex Mixer is a variable speed analog mixer that is designed for continuous duty. The heavy-duty design and efficient motor allow this mixer to operate in continuous duty and handle all accessories over the entire speed range. Choose from two modes of operation: "Touch" mode for mixing tubes when cup head or Universal Holder with cover is depressed, or "On" mode when using any of the accessory attachments for continuous operation.

Operating Conditions:

Unit can be run in conditions from 4 to 40°C, 20% to 85% relative humidity, non-condensing.

Ordering Information:

Mixer includes a cup head, universal holder with cover, foam microtube insert for (38) 1.5 to 2.0 mL microtubes, and a detachable, 3-wire cord and specified plug. Additional accessories can be found on page 60.



This product includes:

Description	Item Number
Cup Head	30400210
Universal Holder	30400226
Universal Holder Cover	30400225
Foam Insert (1.5 to 2.0 microtubes)	30400217



Specifications		
Speed Range	On Mode	300 to 2500 rpm
	Touch Mode	300 to 3500 rpm
Orbit	4.9 mm	
Controls	Analog	
Capacity	1.1 kg	
Duty Rating	Continuous duty	
Dimensions (L × W × H)	24.1 × 16.8 × 16 cm	
Ship Weight	6.8 kg	

Description	Model	Item Number
Analog Heavy Duty Vortex Mixer	VXHDAL	30392141



WolfLabs

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.

www.wolflabs.co.uk

Tel : 01759 301142

Fax : 01759 301143

sales@wolflabs.co.uk

Please contact us if this literature doesn't answer all your questions.